



INDUSTRIAL PREMIUM



DESCRIPTION

PREMIUM series consists of high quality, refined mineral oils of high viscosity index. They contain anti-oxidant, anti-corrosion and anti-foam inhibitors.

APPLICATIONS

PREMIUM series oils are suitable for general machinery lubrication and simple hydraulic and circulations systems and vacuum pumps, which operate under moderate temperature and load conditions, and where there is no need for antiwear protection.

CHARACTERISTICS-BENEFITS

CHARACTERISTICS	BENEFITS
High viscosity index.	Stable viscosity in temperatures variations.
Excellent lubrication performance.	Protection against rust and oxidation.
Very good demulsification and anti-foaming properties.	Smooth system operation.

PHYSICAL-CHEMICAL CHARACTERISTICS

PREMIUM	METHOD	SAE 10W	SAE 30	SAE 40
Density at 15°C, g/cm ³	ASTM D1298	0,8605	0,8800	0,8850
Viscosity, Kinematic (cSt) 40 ⁰ C	ASTM D445	28	88	142
Viscosity, Kinematic (cSt) 100 ⁰ C	ASTM D445	5,2	10,2	14
Viscosity index	ASTM D2270	100	97	96
Flash point, COC, °C	ASTM D92	212	250	258
Pour point, °C	ASTM D97	-27	-24	-15

The above mentioned characteristics represent mean values.