

TECHNICAL PRODUCT SHEET

# CYCLONFLU PLUS



## DESCRIPTION

CYCLONFLU PLUS is a ready-to-use monoethylene glycol-based, hybrid technology (carboxylate/silicate) antifreeze solution in de-ionized water. CYCLONFLU PLUS (35% of antifreeze in water) offers antifreezing protection down to  $-21^{\circ}$  reinforced with special anticorrosion and antirust additives. It protects brass, copper, solder, steel, cast iron, aluminum, and other metals commonly found in industrial cooling and heating systems. By protecting against the "cold" and heat, they are suitable for use all year around.

## APPLICATIONS

CYCLONFLU PLUS is recommended for use in cooling systems of all types of liquid-cooled automotive and industrial internal combustion engines such as car radiators, solar water heating systems and other closed-water circuits operating under extreme temperature conditions. When replacing, it is best preferred to drain the old content before the new filling.

## SPECIFICATIONS

AFNOR NF R15-601: 2020  
ASTM D3306  
ASTM D4985  
SAE J1034  
AS 2108  
FVV Heft R443  
*Meets:*  
VW Group TL-774C (G11)  
MB/DBL 7700.20

BS 6580: 2010  
ASTM D4656  
NATO S-759  
UNE 26361-88  
CUNA NC 956-16

MB 326.0  
MAN 324 NF

## PROPERTIES

CYCLONFLU PLUS provides antifrost protection down to  $-21^{\circ}\text{C}$  while ensuring strong resistance against rust, corrosion, and summer overheating. This ready-to-use coolant is formulated for reliable thermal performance and is fully compatible with the primary elastomer materials used in modern cooling systems.

b



### TECHNICAL PRODUCT SHEET

## PHYSICAL-CHEMICAL CHARACTERISTICS

CYCLONFLU PLUS	METHOD	
Density at 20°C, g/cm <sup>3</sup>	ASTM D5931	1.055
Freezing point, °C	ASTM D1177	-21
Boiling point, °C	ASTM D1120	105
Color		Green

The abovementioned characteristics represent mean values.

## STORAGE

All packages must be stored in covered, well-ventilated areas. If outdoor storage cannot be avoided, barrels must be placed horizontally to prevent water ingress and to protect labels and markings from damage. Products must not be stored at temperatures above 60 °C and must not be exposed to direct sunlight, freezing conditions, or extreme temperature fluctuations.



## HEALTH & SAFETY

This product is not considered to pose significant risks to health or safety when used as intended and in accordance with recommended personal hygiene practices. It must not be applied for purposes other than those for which it has been formulated. For detailed guidance on safe handling and use, refer to the Safety Data Sheet (SDS).



## USED OILS

Used lubricants must be collected at designated collection points to prevent environmental contamination. They must not be mixed with solvents, brake fluids, or antifreeze.

